



FEATURES

Max absorbed power: 70 W
Air flow (max): 300 m³/h
Max air speed: 5,2 m/s
Max power noise level: 62 dB(A)
3 power settings
Removable tank 6 Lt
Timer 1/2/3 h
Washable fabric antidust filter
With automatic swing of the horizontal flaps
Manual adjustment of the vertical flaps
High capacity tank
Compact design




COMPACTNESS

Compact, space-saving design.



REMOVABLE TANK

Easy to fill and clean.



ANTIDUST FILTER

Washable Fabric Antidust filter.



SILENT SYSTEM

		PELER 6E
Product code		99428
Power supply	V/ph/Hz	220-240 / 1 / 50
Maximum power absorption	W	70
Stand-by power consumption	W	0,4
Fan speeds	n	3
Air volume (maximum)	m ³ /h	300
Air speed (maximum)	m/s	5,2
Sound pressure level (1)	dB (A)	37 - 45
Maximum Sound power level (1)	dB (A)	 62
Degrees of protection provided by enclosures		-
Insulation class		II
Power cable	n / mm ²	2 x 0,75
Water tank capacity	l	6,0
Evaporative sheet		honeycomb
Control panel		buttons
Maximum remote control range (distance / angle)	m / °	-
Conformity Mark		CE
Certification Mark		Intertek
Product size (W x H x D)	mm	238x683x302
Gift box size (W x H x D)	mm	286x745x340
Weight (without packing)	kg	5,4
Weight (with packing)	kg	7,0
Units per master box	n	-
Master size (W x H x D)	mm	-
Timer		1, 2, 4 or 3 hours
Removable water tank		√
Oscillating function		YES of horizontal air flow flaps
Remote controller		-
Ionizer		-
Wall support		-
Power supply cable housing		-

(1) Test condition: The sound pressure level is measured in half-anechoic room far 2 meters from the front of the appliance with the microphone at 1 meter of height. During the test, all the appliance functions are enabled with the exception of swing function (if available)