

CALDO UP T

Programmable wall-mounted ceramic fan heater

Cod. 99364



LED DISPLAY

Option to view the temperature and active functions via LED indicator lights on-board the machine.



COMFORT 12 MONTHS

Three operating levels with fan only and two power levels, with motorised flap and auto-swing



SECURE SYSTEM

Safety thermostat, overheating protection and window opening detector



2000W WITH CERAMIC TECHNOLOGY

The ceramic resistance guarantees more even and constant heat distribution.

FEATURES

- Max power : 2000 W
- Ceramic resistance
- 3 settings: fan only/low/high
- Remote control
- LED display with digital controls
- Weekly timer with daily slots
- Overheating protection
- Practical wall connection
- Automatic flap swing
- Light power indicator
- Weekly programming timer
- Open window detector



CALDO UP T WIFI

Programmable wall-mounted ceramic fan heater

Cod. 99261



WI-FI E VOICE CONTROL

Thanks to the integrated Wi-Fi and compatibility with the most common voice controllers, it can be managed with either voice commands or using the dedicated app.



COMFORT 12 MONTHS

Three operating levels with fan only and two power levels, with motorised flap and auto-swing



SECURE SYSTEM

Safety thermostat, overheating protection and window opening detector



2000W WITH CERAMIC TECHNOLOGY

The ceramic resistance guarantees more even and constant heat distribution.

FEATURES

- Max power : 2000 W
- Ceramic resistance
- 3 settings: fan only/low/high
- Remote control
- LED display with digital controls
- Weekly timer with daily slots
- Overheating protection
- Practical wall connection
- Automatic flap swing
- Light power indicator
- Weekly programming timer
- Open window detector



Technical specifications ceramic fan heaters

		CALDO UP T	CALDO UP T WIFI
PRODUCT CODE		99364	99261
EAN CODE		8021183992618	8021183992618
Thermal power (Max)	W	2000	2000
Power settings		ONLY FAN / 1000 / 2000	ONLY FAN / 1000 / 2000
Heating volume (max)	m ³	60	60
Dimensions (WxHxD)	mm	560 x 185 x 145	560 x 185 x 145
Gift box dimensions (WxHxD)	mm	595 x 225 x 170	595 x 225 x 170
Master dimensions (W x H x D)	mm	605 x 355 x 470	605 x 355 x 470
Units per master		4	4
Weight (without packaging)	kg	2,8	2,8
Weight (with packaging)	kg	3,1	3,1
Insulation class		II	II
Degree of protection provided by covers		IP X0	IP X0
Electrical power supply	V-F-Hz	220/240 - 1 - 50	220/240 - 1 - 50
Conformity mark		CE	CE
Ceramic resistance		√	√
Timer		√	√
Room thermostat		√	√
Safety thermostat		√	√
Ventilation function		√	√
Oscillating function		√	√
Anti-turn over switch		-	-
Anti-ice function		-	-
Power selector		√	√
Remote control		√	√
Tilt adjustment		-	-
LED indicators		√	√
Eco Function		-	-
Integrated wi-fi & voice control			√