

Cod. 02106

Cod. 02107



SUPER POWER

Seccoprof is able to absorb up to 40 litres of excess humidity per day, thus allowing the dehumidification of large spaces.



NON-STOP OPERATING

Continuous condensate drain for non-stop dehumidification, without needing to remove the tank.



WARM GAS DEFROSTING

Guarantees constant operation of the compressor, avoiding frequent activation and deactivation periods, and also allows operation at temperatures close to 0°C.



DIGITAL CONTROL

The control panel allows accurate settings and timely control of the air temperature and humidity.

FEATURES

Dehumidification capacity: 30l / 24h and 40l / 24h
For rooms up to 150/200 m³

Coolant gas: R290

Tank capacity: 8l

Noise level 52 dB

Temperature and humidity indicator

1-24h timer

Removable tank with water level visualisation

2 fan speed levels

Dry and Fan function

Automatic defrosting device

Wheels for transportation

Full tank alarm

2 filtering levels (pre-filter / activated carbon filter)



PRODUCT CODE		SECCOPROF 30 P	SECCOPROF 40 P
EAN CODE		02106	02107
Dehumidification capacity (1)	l/24h	30	40
Power absorption in dehumidification mode (1)	W	560	650
Max. power absorption in dehumidification mode (U.L.U.)	W	620	750
Fan speed	nr	2	2
Tank capacity	l	8	8
Air volume (max)	m³/h	240	240
Sound pressure	dB(A)	52	52
Dimensions (WxHxD)	mm	312 x 635 x 453	312 x 635 x 453
Gift box dimensions (WxHxD)	mm	356 x 688 x 492	356 x 688 x 492
Weight (without packaging)	kg	24,9	27,2
Weight (with packaging)	kg	26,8	29,0
Refrigerant gas / Charge (kg)		R290 / 0,083	R290 / 0,096
Power supply	V-F-Hz	220-240 - 1 - 50	220-240 - 1 - 50
Plug		Schuko	Schuko
Power supply min - max	V	220-240	220-240
Antidust filter		✓	✓
Carbon filter		✓	✓
HEPA filter		-	-
Continuous operation with hose		✓	✓
Digital control		✓	✓
Humidity level power settings		✓	✓
LCD Display		✓	✓
Indoor humidity visualizer		✓	✓
Indoor temperature visualizer		✓	✓
Full tank alarm		✓	✓
Defrosting device		✓	✓
Mot gas defrosting system		✓	✓
Handle		✓	✓
Wheels		✓	✓
Tank with push-pull locking		-	-
Tank with Handle		-	-
Visible water level		✓	✓

(1) DB 32°C - WB 29°C (32°C-80%)
(U.L.U.) DB 35°C - WB 31°C (35°C-80%)