PELER 5





Max absorbed power: 50 W Air flow (max): 400 m³/h Max air speed: 1,1 m/s Max power noise level: 60 dB(A) Water tank capacity: 5,0 l Swing function Removable tank Remote control







REMOTE CONTROL Removable remote control for more practicality







ANTIDUST FILTER Washable Fabric Antidust filter.



		PELER 5
Product code		99454
Power supply	V/ph/Hz	220-240 / 1 / 50
Maximum power absorption	W	50
Stand-by power consumption	W	0,5
Fan speeds	n	3
Air volume (maximum)	m³/h	400
Air speed (maximum)	m/s	1,1
Sound pressure level (1)	dB (A)	37 - 45
Maximum Sound power level (1)	dB (A)	■ 60
Degrees of protection provided by enclosures		-
Insulation class		II
Power cable	n / mm²	2 x 0,75
Water tank capacity	1	5,0
Evaporative sheet		cloth
Control panel		touch
Maximun remote control range (distance / angle)	m / °	6
Conformity Mark		CE
Certification Mark		Intertek - GS
Product size (W x H x D)	mm	260x959x260
Gift box size (W x H x D)	mm	310x1020x315
Weight (without packing)	kg	6,0
Weight (with packing)	kg	7,0
Units per master box	n	-
Master size (W x H x D)	mm	-
Timer		1, 2, 4 or 8 hours
Removable water tank		\checkmark
Oscillating function		YES of top column
Remote controller		\checkmark
lonizer		-
Wall support		-
Power supply cable housing		-

(1) Test condition: The sound pressure level is measured in half-anechoic room far 2 meters from the front of the appliance with the microphone at 1 meter of height. During the test, all the appliance functions are enabled with the exception of swing function (if available)