CALDOSILENT ECO



FEATURES

Needles resistance Superpower: max thermal output 2400 W 2 power settings (1200-2400W) Fan only function Mechanical control IP 21 certification gainst water dripping Safety thermostat Room Thermostat Anti-frost function Handle Max room volume: 80 m³



<u>supersilent</u> Exclusive technology, designed in Italy Guaranteed hot and silence



SUPER SILENT Llower sound pressure: up to 3dB (A) less than traditional models. 50%* lower perceived noise.



WATER SAFETY: IP 21 IP 21 approved to ensure safety against vertical

water dripping. Thanks to the special grille design and the shielding of the internal components the product can be used even in the bathroom.



Among the most powerful of its category, up to 2200 Ŵ.









| | | CALDOSILENT ECO |
|--|--------|-----------------|
| | Cod. | 99451 |
| | EAN | 8021183994513 |
| Thermal power (min - max) | W | 2400 |
| Power setting | W | 0 / 1200 / 2400 |
| Heating volume (max) | m³ | 80 |
| Dimensions (without packaging) (W x H x D) | mm | 267x343x251 |
| Dimensions (with packaging) (Larg. x Alt. x Prof.) | mm | 285x360x265 |
| Weight (without packaging) | kg | 2,7 |
| Weight (with packaging) | kg | 3,0 |
| Insulation class | | II |
| Protection level | | IP 21 |
| Ventilation speed | | 1 |
| Power supply | V-F-Hz | 230 - 1 - 50 |
| Power cable | | 2 x 1 |
| Conformity Mark | | CE |
| Needles resistance | | \checkmark |
| 24h Timer | | |
| Room thermostat | | \checkmark |
| Safety thermostat | | \checkmark |
| Fan only Function | | \checkmark |
| Wall mount | | |
| Oscillation | | |
| Turnover protection switch | | |
| Anti-frost function | | \checkmark |
| Power setting | | \checkmark |
| Housign for power cable / cable winder | | |