


# CALDOSTILE M

Modern, compact and easy-to-use ceramic fan heater

Cod. 99448



## AIR FILTER

Air filter with antidust efficiency, easy to remove and clean



## 3 MODES OF USE

Only fan - 2 power level.



## ANTI-FROST FUNCTION

To set automatic ignition, when the temperature drops below 5°C



## 2000W WITH CERAMIC TECHNOLOGY

The ceramic resistance guarantees more even and constant heat distribution.

## FEATURES

- Max thermal output: 2000 W
- 2 power level (1200 - 2000 W)
- Ceramic Resistance
- Room Thermostat
- Safety thermostat
- Only fan function
- Anti-frost function
- Power selection
- Mechanical control
- Antidust filter



# Technical specifications ceramic fan heaters

		CALDODESIGN	CALDODESIGN O	CALDODESIGN S	CALDO TRENDY	CALDO TRENDY ST	CALDO TRENDY T
<b>PRODUCT CODE</b>		99447	99402	99404	99268	99267	99266
<b>EAN CODE</b>		8021183994476	8021183994025	8021183994049	8021183992687	8021183992670	8021183992663
Thermal power (Max)	W	1800	1800	1800	1800	2000	2000
Power settings		ONLY FAN / 1000 / 1800	ONLY FAN / 1000 / 1800	ONLY FAN / 1000 / 1800	900 / 1800	1000 / 2000	1000 / 2000
Heating volume (max)	m³	55	55	55	55	60	60
Dimensions (WxHxD)	mm	245 x 248 x 216	245 x 248 x 216	245 x 248 x 216	216 x 284 x 125	190 x 450 x 140	241 x 604 x 190
Gift box dimensions (WxHxD)	mm	275 x 275 x 235	275 x 275 x 235	275 x 275 x 235	262 x 316 x 150	232 x 486 x 183	278 x 655 x 225
Master dimensions (W x H x D)	mm	750 x 290 x 570	750 x 290 x 570	750 x 290 x 570	465 x 647 x 277	387 x 511 x 250	465 x 670 x 293
Units per master		6	6	6	6	2	2
Weight (without packaging)	kg	1,8	1,8	1,8	1,7	2,5	3,2
Weight (with packaging)	kg	2,2	2,2	2,2	2,0	3,0	3,8
Insulation class		II	II	II	II	II	II
Degree of protection provided by covers		IP X0	IP X0	IP X0	IP21	IPX0	IPX0
Electrical power supply	V-F-Hz	220/240 - 1 - 50	220/240 - 1 - 50	220/240 - 1 - 50	220/240 - 1 - 50	220/240 - 1 - 50	220/240 - 1 - 50
Conformity mark		CE	CE	CE	CE	CE	CE
Ceramic resistance		√	√	√	√	√	√
Timer		-	-	-	√	√	√
Room thermostat		√	√	√	√	√	√
Safety thermostat		√	√	√	√	√	√
Ventilation function		√	√	√	-	-	-
Oscillating function		-	-	-	√	√	√
Anti-turn over switch		-	-	-	√	√	√
Anti-ice function		√	√	√	-	-	-
Power selector		√	√	√	√	√	√
Remote control		-	-	-	-	√	√
Tilt adjustment		√	√	√	-	-	-
LED indicators		√	√	√	√	√	√
Eco Function		-	-	-	√	√	√
Integrated wi-fi & voice control		-	-	-	-	-	-

		CALDOSTILE M	CALDOSTILE D	CALDOSTILE DT	CALDO SKY B WIFI	CALDO SKY G WIFI	CALDO UP T
<b>PRODUCT CODE</b>		99448	99449	99450	99264	99265	99364
<b>EAN CODE</b>		8021183994483	8021183994490	8021183994506	8021183992649	8021183992656	8021183993646
Thermal power (Max)	W	2000	2000	2200	2000	2000	2000
Power settings		ONLY FAN / 1200 / 2000	ONLY FAN / 1200 / 2000	ONLY FAN / 1100 / 2200	ONLY FAN / 1000 / 2000	ONLY FAN / 1000 / 2000	ONLY FAN / 1000 / 2000
Heating volume (max)	m³	60	60	75	60	60	60
Dimensions (WxHxD)	mm	210 x 305 x 158	238 x 337 x 173	215 x 548 x 215	550 x 180 x 125	550 x 180 x 125	560 x 185 x 145
Gift box dimensions (WxHxD)	mm	240 x 335 x 188	268 x 367 x 203	245 x 578 x 245	598 x 220 x 156	598 x 220 x 156	595 x 225 x 170
Master dimensions (W x H x D)	mm	690 x 391 x 495	754 x 421 x 551	503 x 595 x 503	610 x 330 x 460	610 x 330 x 460	605 x 355 x 470
Units per master		8	8	4	4	4	4
Weight (without packaging)	kg	1,4	1,8	2,6	2,3	2,3	2,8
Weight (with packaging)	kg	1,8	2,2	3,2	2,6	2,6	3,1
Insulation class		II	II	II	II	II	II
Degree of protection provided by covers		IP X0	IP X0	IP X0	IP22	IP22	IP X0
Electrical power supply	V-F-Hz	220/240 - 1 - 50	220/240 - 1 - 50	220/240 - 1 - 50	220/240 - 1 - 50	220/240 - 1 - 50	220/240 - 1 - 50
Conformity mark		CE	CE	CE	CE	CE	CE
Ceramic resistance		√	√	√	√	√	√
Timer		-	√	√	√	√	√
Room thermostat		√	√	√	√	√	√
Safety thermostat		√	√	√	√	√	√
Ventilation function		√	√	√	√	√	√
Oscillating function		-	√	√	√	√	√
Anti-turn over switch		-	√	√	-	-	-
Anti-ice function		√	√	√	-	-	-
Power selector		√	√	√	√	√	√
Remote control		-	√	√	√	√	√
Tilt adjustment		√	-	-	-	-	-
LED indicators		√	√	√	√	√	√
Eco Function		-	√	√	-	-	-
Integrated wi-fi & voice control		-	-	-	√	√	-